

HOOK-UP & LEAD WIRE

Single Conductor Thermoset Insulated Multi-Rated 3340/3374

DESCRIPTION

Single Conductor Thermoset Insulated Multi-Rated 3340/3374
 UL AWM 3340 OR 3374 125C (FLEX)/150C (NO-FLEX) 600V
 CSA CL1503 OR AWM I A/B 125C 600V FT2

Sizes

#20 AWG - #4/0 AWG.

Insulation

Thermoset

APPLICATIONS

Can be used for appliances, motor lead, coil lead, transformers, UPS, load banks, electric fork lift, or panel construction.

PART NUMBER	AWG	STRANDING	NOMINAL O.D.	NOMINAL WALL	APPROX. LBS/M FT	UL STYLE	CSA STYLE
05-0323	20	10/30 Tinned Copper	.127	.045	9	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0325	18	16/30 Tinned Copper	.140	.045	12	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0327	16	24/30 Tinned Copper	.153	.045	16	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0329	14	41/30 Tinned Copper	.168	.045	22	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0331	12	65/30 Tinned Copper	.187	.045	30	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0333	10	105/30 Tinned Copper	.216	.045	46	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0335	8	7x12/27 Tinned Copper	.297	.060	79	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0337	6	7x19/27 Tinned Copper	.345	.060	112	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0339	4	7x19/25 Tinned Copper	.392	.060	168	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0341	2	7x19/23 Tinned Copper	.465	.060	264	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0343	1	7x37/25 Tinned Copper	.547	.080	345	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0345	1	7x119/30 Tinned Copper	.547	.080	322	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0347	1/0	7x37/24 Tinned Copper	.596	.080	400	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0349	2/0	19x70/30 Tinned Copper	.620	.080	491	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0351	3/0	19x88/30 Tinned Copper	.694	.080	590	AWM 3340 OR 3374	CL1503 OR AWM I A/B
05-0353	4/0	19x111/30 Tinned Copper	.720	.080	742	AWM 3340 OR 3374	CL1503 OR AWM I A/B

> Information on this sheet is subject to change without notice. All diameters are nominal values. All diameters and weights are subject to normal manufacturing tolerances.

Additional stranding versions available.