

HOOK-UP & LEAD WIRE

1028/1231/1232/1283/1284 MTW (BARE COPPER)

DESCRIPTION

Polyvinylchloride (PVC) Machine Tool Wire (MTW)/Thermoplastic Equipment Wire (TEW) (90°C MTW) (UL & CSA 105°C) (VW-1 & Moisture Resistant) (600 Volts)

Sizes

#8 AWG - #4/0 AWG.

Insulation

Polyvinylchloride

APPLICATIONS

Can be used for control cabinets, internal wiring of appliances and for machine tools.

PART NUMBER	AWG	STRANDING	NOMINAL INSULATION	NOMINAL O.D.	APPROX. LBS/K FT	UL STYLE
05-0079	8	19/.0295 Bare	.045	.239	70	1028/1231
05-0080	8	133/29 Bare	.045	.260	71	1028/1232
05-0081	8	168/30 Bare	.045	.264	72	1028/1231
05-0083	6	19/.0372 Bare	.060	.320	108	1232/1283
05-0084	6	133/27 Bare	.060	.335	115	1232/1283
05-0085	6	259/30 Bare	.060	.337	117	1232/1283
05-0087	4	19/.0469 Bare	.060	.360	161	1232/1283
05-0088	4	133/25 Bare	.060	.370	168	1232/1283
05-0089	4	420/30 Bare	.060	.380	175	1232/1283
05-0091	2	19/.0591 Bare	.060	.411	241	1232/1283
05-0092	2	133/23 Bare	.060	.433	250	1232/1283
05-0093	2	665/30 Bare	.060	.456	263	1232/1283
05-0094	1	133/22 Bare	.080	.550	350	1232/1284
05-0095	1	836/30 Bare	.080	.560	342	1232/1284
05-0096	1/0	133/21 Bare	.080	.620	380	1232/1284
05-0097	1/0	1045/30 Bare	.080	.630	419	1232/1284
05-0098	2/0	133/20 Bare	.080	.650	510	1232/1284
05-0099	2/0	1330/30 Bare	.080	.660	537	1232/1284
05-0100	3/0	259/22 Bare	.080	.670	622	1232/1284
05-0101	3/0	1672/30 Bare	.080	.680	672	1232/1284
05-0102	4/0	259/21 Bare	.080	.780	790	1232/1284
05-0103	4/0	2109/30 Bare	.080	.800	819	1232/1284

> Information on this sheet is subject to change without notice. All diameters are nominal values. All diameters and weights are subject to normal manufacturing tolerances.

See Color Code, Chart 4, for stocked colors available.



PITTSBURGH WIRE & CABLE INC.

www.pittsburghwire.com

Sales and Ordering: 1-800-458-1222