

HOOK-UP & LEAD WIRE

3321

DESCRIPTION

Chemically Cross-linked Polyolefin Insulation (XLP) (150°C)
(600 Volts) (UL & CSA)

Sizes

#20 AWG - #8 AWG.

Insulation

Polyolefin Insulation

APPLICATIONS

Can be used in appliances, transformers, electrical & gas heating, motors, ballast, lighting, hairdressing and cooking equipment.

PART NUMBER	AWG	STRANDING	NOMINAL INSULATION	NOMINAL O.D.	APPROX. LBS/K FT	UL STYLE	C.S.A. TYPE
05-0167	20	10/30 Tinned	.030	.107	7	3321	CL1503/AWM
05-0169	18	16/30 Tinned	.030	.109	10	3321	CL1503/AWM
05-0171	16	26/30 Tinned	.030	.125	13	3321	CL1503/AWM
05-0173	14	41/30 Tinned	.030	.140	19	3321	CL1503/AWM
05-0175	12	65/30 Tinned	.030	.160	28	3321	CL1503/AWM
05-0177	10	105/30 Tinned	.030	.188	43	3321	CL1503/AWM
05-0179	8	133/29 Tinned	.045	.260	75	3322	CL1503/AWM

> Information on this sheet is subject to change without notice. All diameters are nominal values. All diameters and weights are subject to normal manufacturing tolerances.

See Color Code, Chart 4, for stocked colors available.



PITTSBURGH WIRE & CABLE INC.

www.pittsburghwire.com

Sales and Ordering: 1-800-458-1222