

HIGH TEMPERATURE

SFF-2 SEWF-2

**Silicone Rubber Glass Braid Fixture Wire
Flexible Stranded Conductors
600 Volts, 150° C, #18 AWG - #10 AWG**



DESCRIPTION

Conductor

Flexible stranded tinned, annealed copper per ASTM B33.

Sizes

#18 AWG - #10 AWG.

Insulation

Silicone Rubber. A fiberglass braid jacket is applied over the insulation, then treated with a high-temp finish. This product is available in a wide range of colors.

APPLICATIONS

Used for internal wiring of appliances, electrical equipment, and lighting fixtures.

APPROVALS

18 AWG - 14 AWG are UL approved as fixture wire (SFF-2).

UL appliance wire approvals as listed. CSA approved as equipment wire (SEWF-2) as well as appliance wire.

PART NUMBER	AWG	STRANDING	INSULATION THICK.	BRAID THICK.	NOMINAL O.D.	WEIGHT LBS/K FT	UL STYLE	TEMP RATING
08-0089	18	16/.0100	0.030	.005	0.120	13	3070/SFF-2	150°C
08-0091	16	26/.0100	0.030	.005	0.130	17	3070/SFF-2	150°C
08-0093	14	41/.0100	0.030	.005	0.145	23	3070/SFF-2	150°C
08-0095	12	65/.0100	0.030	.005	0.160	32	3070	150°C
08-0097	10	105/.0100	0.045	.005	0.220	53	3101	150°C

> Information on this sheet is subject to change without notice. All diameters are nominal values. All diameters and weights are subject to normal manufacturing tolerances.



PITTSBURGH WIRE & CABLE INC.

www.pittsburghwire.com

Sales and Ordering: 1-800-458-1222